



4 Litre size available

## Unstimulated Water Baths

**FL08D**

**FL14D**

**FL22D**

**FL28D**

**FL56D**

### TEMPERATURE

Display	Digital LED / 0.1°C				
Range	Ambient +5°C - 99°C				
Control	PID - with adaptive /optimisation control				
Sensitivity / Uniformity @ 55°C	±0.2°C Sensitivity / ±0.1°C Uniformity				
Over temp. alarm	+4°C with heater cut-off indication				

### TIMER

Display/resolution	1 minute				
Settings	Variable 0-999 minutes				
Cycle End	audible buzzer and 'end' message				

### GENERAL

Capacity Litres / Voltage* / Watts	8L / 230V / 800W	14L / 230V / 1000W	22L / 230V / 1500W	28L / 230V / 1500W	56L / 230V / 2500W
Working Dimensions (mm)	300w x 240d x 150h	325w x 300d x 150h	500w x 300d x 150h	500w x 300d x 200h	620w x 500d x 200h
Overall Dimensions (mm)	332w x 270d x 290h	361w x 332d x 290h	538w x 332d x 290h	538w x 332d x 290h	660w x 540d x 290h
Drain Tap	Yes	Yes	Yes	Yes	Yes
Lid	Yes	Yes	Yes	Yes	Yes (2 Lids Supplied)

\*120V Models Available



## Unstimulated DuoBaths

4/4 Litre and 4/8 sizes available

**FLD-8/8**

**FLD-4/22**

**FLD-8/22**

### TEMPERATURE

Display	Digital LED / 0.1°C		
Range	Ambient +5°C - 99°C		
Control	PID - with adaptive /optimisation control		
Sensitivity / Uniformity @ 55°C	±0.2°C Sensitivity / ±0.1°C Uniformity		
Over temp. alarm	+4°C with heater cut-off indication		

### TIMER

Display/resolution	1 minute		
Settings	Variable 0-999 minutes		
Cycle End	audible buzzer and 'end' message		

### GENERAL

Capacity Litres / Voltage* / Watts	8+8L / 230V / 1600W	4+22L / 230V / 1900W	8+22L / 230V / 2300W
Working Dimensions (mm)	240w x 300d x 150h & 240w x 300d x 150h	150w x 300d x 150h & 500w x 300d x 150h	240w x 300d x 150h & 500w x 300d x 150h
Overall Dimensions (mm)	600w x 332d x 290h	710w x 332d x 290h	800w x 332d x 290h
Drain Tap	Yes (both chambers)	Yes (22 litre side only)	Yes (both chambers)
Lids	Yes	Yes	Yes

\*120V Models Available



## Stirred Water Baths

Heater Stirrer available for use with stock pots  
- more information provided upon request

**FL414D**

**FL422D**

**FL428D**

### TEMPERATURE

Display	Digital LED / 0.1°C		
Range	Ambient +5°C - 99°C		
Control	PID - with adaptive /optimisation control		
Sensitivity / Uniformity @ 55°C	±0.1°C Sensitivity / ±0.01°C Uniformity		
Over temp. alarm	+4°C with heater cut-off indication		

### TIMER

Display/resolution	1 minute		
Settings	Variable 0-999 minutes		
Cycle End	audible buzzer and 'end' message		

### GENERAL

Capacity Litres / Voltage* / Watts	14L / 230V / 1250W	22L / 230V / 1250W	28L / 230V / 1250W
Working Dimensions (mm)	219w x 298d x 150h	395w x 298d x 150h	395w x 298d x 200h
Overall Dimensions (mm)	361w x 332d x 170h	537w x 332d x 170h	537w x 332d x 240h
Lid	Yes	Yes	Yes

\*120V Models Available