



## FL56D ~ 56 litre digital sous vide bath

For consistent controlled cooking, Clifton water baths allows chefs to cook in a precise temperature controlled environment, to produce consistently perfect results. Ideal for sous vide and other low temperature cooking, these baths are an indispensable piece of equipment for all leading chefs worldwide.

This large bath is particularly suitable for banqueting, outside catering and other high volume operations.

### **Precise temperatures**

Using the same high precision controller found on all other Clifton Food Range products, accuracy and repeatability are guaranteed. Actual temperature is clearly displayed to 0.1°C. If required, the integrated timer can be set between 1 minute and 99 hours. There is audio/visual notification at the end of the set period after which the bath still continues to operate at the set temperature. Current time and temperature settings are retained in memory even after 'power off.'

### **High quality build and features**

Temperatures can be easily and rapidly set with the push button, wipe clean control panel. The entire case is constructed from high quality stainless steel.

If the water drops below the recommended minimum level or the unit is inadvertently switched on without being filled with water, 'FILL' appears on the display as a visual alert and gives run dry protection.

Side lifting handles make it easy to carry the bath around the kitchen and the drain tap allows quick emptying for cleaning. The product is supplied with two stainless steel lids which have easy grab insulated handles. The bath is also supplied with a removable stainless steel perforated shelf which provides effective distribution of heat uniformly throughout the chamber by convection.

In common with all Clifton baths, the product is powered from a standard 13 amp wall socket.

## Temperature

---

Display/resolution:	Digital LED/ 0.1°C
Temp. range:	Ambient + 5°C - 95°C
Temp. setting:	Pushbutton
Stability/uniformity:	± 0.2°C / ±0.1°C

## Timer:

---

Display/resolution:	Digital LED / 1 minute increments
Duration:	1 minute – 99 hours
Cycle end:	Audio/visual alert

## General:

---

Dimensions (mm):	overall - 660w x 540d x 290h working - 620w x 500d x 200h
Electrical supply:	230v
Power consumption:	2.5 kW
Safety:	Visual 'FILL' message on low water level Run-dry protection

Supplied complete with drain tap, lids and stainless steel shelf.

Product shown with accessory P270 and P470 dividers



Manufactured in UK

Clifton Food Range equipment is developed and manufactured by NICKEL-ELECTRO Ltd.  
Oldmixon Crescent, Weston-super-Mare, North Somerset, BS24 9BL, UK.

Tel: +44 (0)1934 626691 Email: [info@cliftonfoodrange.co.uk](mailto:info@cliftonfoodrange.co.uk) [www.cliftonfoodrange.co.uk](http://www.cliftonfoodrange.co.uk)