



## FX Range - Integrated (drop in) Digital Baths

Clifton built-in Water Baths are designed to be installed into the kitchen work surface, freeing countertop space where it is at a premium in a busy kitchen.

### Precise temperatures

Using the same high precision controller found on all other Clifton Food Range<sup>®</sup> products, accuracy and repeatability are guaranteed. Heaters and temperature sensors are concealed under the tank. Integrated timer with audio/visual notifications. Current time and temperature settings are retained in memory even after 'power off.'

### High quality build and features

The space saving bath can be integrated into a new or existing kitchen and easily assembled using the clear, concise instructions. The unit consists of an under-mounted heater on the tank and large bore (38mm diameter) flip top drain, fitted into each tank, for connection to standard waste outlet. Control panel is brushed stainless steel, with fixing holes and graphic overlay.

Controller and tank are pre-calibrated as a matched pair. The underside of the drop-in tank is enclosed to prevent access to the wiring. Installation must be made by a qualified electrician and access should be made available for maintenance by qualified electrical personnel. To assist installation, all electrical and temperature probe connections are clearly marked and fitted with plugs and mating sockets.

Temperature can be easily and rapidly set with the push button, wipe clean control panel mounted on the front of the work surface. If the water in the tank drops below the recommended minimum level or the unit is inadvertently switched on without being filled with water, 'FILL' appears on the display as a visual alert and gives run-dry protection.

Each bath is supplied with a stainless steel lid(s) with insulated handle. Constructed from high quality stainless steel. The bath is also supplied with a removable stainless steel perforated shelf which provides effective distribution of heat uniformly throughout the bath by convection.

## Tank Choice

### FX08D - 8 litre bath

Chamber Dims (mm): Working - 300w x 240d x 150h  
 Watts: 1kW  
 Electrical supply: 230V

Can be selected as a single chamber or duobath™

### FX14D - 14 litre bath

Chamber Dims (mm): Working - 330w x 300d x 150h  
 Watts: 1kW  
 Electrical supply: 230V

Can be selected as a single chamber or duobath™

### FX28D - 28 litre bath

Chamber Dims (mm): Working - 500w x 300d x 200h  
 Watts: 2kW  
 Electrical supply: 230V

Can be selected as a single chamber or duobath™

Can mix and match chambers to create a duobath™

Warranty: 2 years, parts only; on site support is the responsibility of the installation company for integrated baths.

Select the tank(s) required - for single tank order FXC1 controller. For duobath™ order FXC2 controller (regardless of tank size).

For duobath™, mix and match tank size according to your requirements. Controller(s) and tank(s) are purchased separately and supplied pre-calibrated as a matched pair.



## Controller Choice

	FXC1 - Single Chamber Controller	FXC2 - Dual Chamber Controller
<b>Temperature</b>		
Display/resolution	Digital LED / 0.1°C	
Temp. range	Ambient +5°C - 95°C	
Temp. setting	Push button	
Stability/uniformity	± 0.2°C/± 0.1°C	
<b>Timer</b>		
Display/resolution	Digital LED / 1 minute increments	
Duration	1 minute - 99 hours	
Cycle end	Audio / visual alert	
<b>General</b>		
Control panel dims (mm)	357w x 136h	460w x 136h
Control panel choice	Single tank control	Dual tank control
Material	Brushed stainless steel	
Safety	Visual 'Fill' message on low water level. Run dry protection	