



## FLE-8/8 - 8 + 8 litre Compact Digital Duobath™

For consistent controlled cooking, Clifton water baths allows chefs to cook in a precise temperature controlled environment, to produce consistently perfect results. Ideal for sous vide and other low temperature cooking, these baths are an indispensable piece of equipment for all leading chefs worldwide. The duobath™ range allows chefs to use each chamber simultaneously at two different temperatures.

### Versatility

This sous vide bath is a variation on the popular 8 litre duobath™ model. It has the controls placed on the narrow end of the bath meaning that the whole unit can be run from 'front to back' on the counter top. This results in a saving where space is at a premium in a busy kitchen. The drain taps are located on the front panel making it easy to clean down after service.

As with all Clifton duobaths™, each side can be operated at two different temperatures simultaneously and with two different liquids e.g. water in one side and oil in the other.

### Precise temperatures

Using the same high precision controllers found on all other Clifton Food Range® products, accuracy and repeatability are guaranteed. Actual temperature is clearly displayed to 0.1°C. If required, the integrated timer on each controller can be set between 1 minute and 99 hours. There is audio/visual notification at the end of the set period after which the bath still continues to operate at the set temperature. Current time and temperature settings are retained in memory even after 'power off.'

## High quality build and features

Temperatures can be easily and rapidly set with the push button, wipe clean control panel. The entire case is constructed from high quality stainless steel. If the water drops below the recommended minimum level or the unit is inadvertently switched on without being filled with water, 'FILL' appears on the display as a visual alert and gives run-dry protection. If desired it is possible to switch off one of the controllers to allow only one chamber of the duobath™ to be used.

The side lifting handles are offset to ensure that the bath is balanced when carried around the kitchen. The bath is supplied with two lids which have easy grab insulated handles, and two removable stainless steel perforated shelves, which provide effective distribution of heat uniformly throughout the chambers

Drain tap on each chamber. In common with all Clifton baths, the product is powered from a standard 13 amp wall socket.

## Temperature

Display/resolution:	Digital LED/0.1°C
Temp. range:	Ambient + 5°C - 95°C
Temp. setting:	Push button
Stability/uniformity:	± 0.2°C/± 0.1°C

## Timer

Display/resolution:	Digital LED/1 minute increments
Duration:	1 minute - 99 hours
Cycle end:	Audio/visual alert

## General

Dimensions (mm):	Overall - 336w x 537d x 332h Working - 300w x 242d x 150h (each chamber) Allow 90mm at rear of unit for mains cable/ventilation Allow 130mm at front of unit for tap & hose
------------------	--

Electrical supply:	230V
Power consumption:	1.6kW
Safety:	Visual 'FILL' message on low water level Run-dry protection

Supplied complete with drain taps, lids and removable shelves

Warranty: 2 years back to base

FLE-8/8 is a registered design that belongs to Nickel-Electro Ltd.  
Design Reg No: 00207 4609-0002